

## **G2L PAPER LoCo 3300e** *tickets for parking & public transportation*

### **GLUE DOWN LAMINATION FOIL, LOW COERCIVITY, INCORPORATING REINFORCED PROTECTIVE LAYER**

G2L magnetic foil uses state of the art Ferric oxide to achieve high signal levels, conforming to ISO7811/2. G2L is a glue down lamination tape specially formulated with a reinforced protective layer within magnetic coating to provide enhanced durability, mark resistance and slip. The unique formula provides a lower coefficient of friction against the read/write heads.

<b>Characteristics</b>	<b>G2L</b>
BASE FILM	Polyester
BASE THICKNESS	12µm
TOTAL THICKNESS	21µm
OXIDE COLOUR	Brown
WINDOW OUTPUT	110%
ACTIVATION TEMP	N/A
SPECIAL FEATURES	Standard Durability
STORAGE	Temperature 10°C - 35°C
	Humidity 40% - 60% RH
HANDLING	Reels should be stored at 20°C for 24 hours before use

AVERAGE READ BACK SIGNAL	80% <= Average Read Back Signal <= 120%
AVERAGE WRITE CURRENT	350% <= Average Write Current <= 500%
ABRASION RESISTANCE	3000 cycles ISO head tester.
RETENTIVITY	135 +/- 10% mT
SQUARENESS Br/Bs	>0.80
REMANENCE	0.95 mx/cm +/- 10.0%